


GF Malleable Fittings 260 - socket eccentric, reduced, black 1 1/2 - 1/2

1153976

- Socket eccentric, reducing



About GF Malleable Fittings 260 - socket eccentric, reduced, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 260 - socket eccentric, reduced, black 1 1/2 - 1/2

1153976



Product code

Item no EAN	7611205327262
Item no GF	770260120
Item no GTIN	07611205327262
Item no RSK	1363716

Dimensions

Item Unit Height	62
Item Unit Length	62
Item Unit Weight	0,289
Item Unit Width	56
Item_UOM	pce

Measurements

Metric thread M	14,0
Z Measurement a	56
Z Measurement a	56
Z	24

Packaging

Packaging GTIN PL1	07611205127268
Packaging GTIN PL4	06414900121651
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	40
Packaging Quantity PL4	2160
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	11,774
Packaging Weight PL4	644,24
Packaging Width PL1	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com