


GF Malleable Fittings socket 1/8 STA

1154005

- Socket, ISO/EN M2

- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations. Steel parts are hexagonal instead of beaded.



About GF Malleable Fittings socket

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings socket 1/8 STA

1154005



Product code

Item no EAN	7611205328061
Item no GF	770270101
Item no GTIN	07611205328061
Item no RSK	1311000
Item no VVS	004270101

Dimensions

Item Unit Height	19
Item Unit Length	19
Item Unit Weight	0,0238
Item Unit Width	25
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205528065
Packaging GTIN PL2	07611205128067
Packaging GTIN PL4	06414900121569
Packaging Height PL1	19
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	135
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	100
Packaging Quantity PL4	7200
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,00135945
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,2426575
Packaging Weight PL2	2,546575
Packaging Weight PL4	208,3534
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Wall thickness_s	17
Z Measurement a	25
Z Measurement a	25
Z Measurement d	1/8
Z MEASUREMENT S	17
z1	11

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com