Product data sheet




GF Malleable Fittings socket 1

1154022

- Socket, ISO/EN M2

- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations. Steel parts are hexagonal instead of beaded.





About GF Malleable Fittings socket

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings socket 1

1154022





Product code

Item no EAN	7611205428235
Item no GF	770270206
Item no GTIN	07611205428235
Item no LVI	0855165
Item no NOBB	60639135
Item no NRF	1366867
Item no RSK	1311208
Item no VVS	004270408

Dimensions

Item Unit Height	46
Item Unit Length	46
Item Unit Weight	0,188
Item Unit Width	45
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205628239
Packaging GTIN PL2	07611205228231
Packaging GTIN PL4	06414900124195
Packaging Height PL1	46
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	270
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10

Packaging Quantity PL2	50
Packaging Quantity PL4	2700
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0065826
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,89
Packaging Weight PL2	9,55
Packaging Weight PL4	540,7
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z Measurement A	45
Z Measurement d	1
z1	11

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+