

GF Malleable Fittings hexagonal nipple 280 3 B

1154064

- Hexagon nipple, ISO/EN N8
- 'ST' these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations.



About GF Malleable Fittings hexagonal nipple 280

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings hexagonal nipple 280 3 B

1154064



Product code

Item no EAN	7611205329204
Item no GF	770280111
Item no GTIN	07611205329204
Item no LVI	0755165
Item no NOBB	60639166
Item no NRF	1366898
Item no RSK	1316405
Item no VVS	004280114

Dimensions

Item Unit Height	100
Item Unit Length	117
Item Unit Weight	1,108
Item Unit Width	83
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205129200
Packaging GTIN PL4	06414900121279
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL4	405
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984

Packaging Weight PL1	17,04
Packaging Weight PL4	468,74
Packaging Width PL1	255
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb