


GF Malleable Fittings plug beaded 290 3/8 B

1154102

- Plug, beaded, ISO/EN T9
- 'ST' these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations.
- * Solid



About GF Malleable Fittings plug beaded 290

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings plug beaded 290 3/8 B

1154102



Product code

Item no EAN	7611205329631
Item no GF	770290103
Item no GTIN	07611205329631
Item no LVI	0755168
Item no NOBB	60639170
Item no NRF	1366902
Item no RSK	1254001
Item no VVS	004290103

Dimensions

Item Unit Height	22
Item Unit Length	24
Item Unit Weight	0,0418
Item Unit Width	28
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205529635
Packaging GTIN PL2	07611205129637
Packaging GTIN PL4	06414900121170
Packaging Height PL1	22
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	135
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	150
Packaging Quantity PL4	10800

Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0015741
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,4226575
Packaging Weight PL2	6,4598625
Packaging Weight PL4	490,1101
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb