


GF Malleable Fittings plug beaded 290 1 1/4 B

1154106

- Plug, beaded, ISO/EN T9
- 'ST' these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations.
- * Solid



About GF Malleable Fittings plug beaded 290

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings plug beaded 290 1 1/4 B

1154106



Product code

Item no EAN	7611205329730
Item no GF	770290107
Item no GTIN	07611205329730
Item no LVI	0755172
Item no NOBB	60639178
Item no NRF	1366910
Item no RSK	1254009
Item no VVS	004290110

Dimensions

Item Unit Height	45
Item Unit Length	49
Item Unit Weight	0,2319
Item Unit Width	47
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205129736
Packaging GTIN PL4	06414900121132
Packaging Height PL1	200
Packaging Height PL4	534
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	70
Packaging Quantity PL4	2520
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,51264

Packaging Weight PL1	16,447
Packaging Weight PL4	604,388
Packaging Width PL1	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb