Product data sheet




GF Malleable Fittings 321 - screwed flange, undrilled, black 2

1154270

- Screwed flange, undrilled





About GF Malleable Fittings 321 - screwed flange, undrilled, black

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 321 - screwed flange, undrilled, black 2

1154270





Status

Item Available From date	2025-09-05

Product code

Item no EAN	7611205333423
Item no GF	770320109
Item no GTIN	07611205333423
Item no RSK	1254087
Item no VVS	004321112

Dimensions

Item Unit Height	140
Item Unit Length	140
Item Unit Weight	1,09
Item Unit Width	22
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205133429
Packaging GTIN PL4	06414900120364
Packaging Height PL1	200
Packaging Height PL4	534
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL4	540
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,51264
Packaging Weight PL1	16,564
Packaging Weight PL4	608,6
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement A	68
Z Measurement b	11
Z Measurement d	140
Z Measurement H	22
Z Measurement k	110

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+