Product data sheet




GF Malleable Fittings 326 - screwed flange, drilled, 2 holes, galvanized 1

1154285

- Screwed flange, drilled, 2 holes





About GF Malleable Fittings 326 - screwed flange, drilled, 2 holes, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 326 - screwed flange, drilled, 2 holes, galvanized 1

1154285





Status

Item Available From date	2025-09-05

Product code

Item no EAN	7611205434649
Item no GF	770326206
Item no GTIN	07611205434649
Item no RSK	1254094
Item no VVS	004326408

Dimensions

Item Unit Height	72
Item Unit Length	100
Item Unit Weight	0,416
Item Unit Width	20
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205234645
Packaging GTIN PL4	06414900241427
Packaging Height PL1	100
Packaging Height PL4	508
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL4	1440
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00494

Packaging Volume PL4	0,48768
Packaging Weight PL1	8,44
Packaging Weight PL4	619,04
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement A	100
Z Measurement A	46
Z Measurement b	11
Z Measurement B	72
Z Measurement d	1
Z Measurement H	20
Z Measurement k	75
Z	3

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+