


GF Malleable Fittings 329 - screwed flange, drilled, 4 holes, black 3 4L

1154296

- Screwed flange, drilled, 4 holes
- Diameter of pitch circle and sealing face compatible to EN 1092-2 and DIN 2566.
- * 4 holes



About GF Malleable Fittings 329 - screwed flange, drilled, 4 holes, black Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 329 - screwed flange, drilled, 4 holes, black 3 4L

1154296



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205335038
Item no GF	770329111
Item no GTIN	07611205335038
Item no RSK	1254115
Item no VVS	004328114

Dimensions

Item Unit Height	200
Item Unit Length	200
Item Unit Weight	3,95
Item Unit Width	36
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205135034
Packaging GTIN PL4	06414900120227
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	4
Packaging Quantity PL4	216
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	16,014

Packaging Weight PL4	873,2
Packaging Width PL1	190
Packaging Width PL4	800
Measurements	
Z Measurement a	115
Z Measurement a	115
Z Measurement b	18
Z Measurement d	200
Z Measurement H	36
Z Measurement k	160
Z	6

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com