


GF Malleable Fittings 336 - union flat seat, black 1/2

1154367

- Union flat seat

- Supplied without sealing gaskets; c includes the seal thickness as per table "Sealing Gasket Dimension".

- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.



About GF Malleable Fittings 336 - union flat seat, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 336 - union flat seat, black 1/2

1154367



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205337148
Item no GF	770336104
Item no GTIN	07611205337148
Item no RSK	1260857
Item no VVS	004336104

Dimensions

Item Unit Height	41
Item Unit Length	45
Item Unit Weight	0,2533
Item Unit Width	85
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205137144
Packaging GTIN PL4	06414900119900
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	60
Packaging Quantity PL4	3240
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	15,412

Packaging Weight PL4	840,692
Packaging Width PL1	190
Packaging Width PL4	800
Measurements	
Wall thickness_s1	26
Wall thickness_s2	41
Wall thickness s3	23
Z Measurement a	43
Z Measurement a	43
Z Measurement b	40
Z Measurement d	1/2

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com