Product data sheet




GF Malleable Fittings 336 - union flat seat, black 1 1/2

1154371

- Union flat seat

- Supplied without sealing gaskets; c includes the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.



About GF Malleable Fittings 336 - union flat seat, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 336 - union flat seat, black 1 1/2

1154371



Status

Item Available From date	2025-09-05

Product code

Item no EAN	7611205337223
Item no GF	770336108
Item no GTIN	07611205337223
Item no RSK	1260865
Item no VVS	004336111

Dimensions

Item Unit Height	74
Item Unit Length	81
Item Unit Weight	0,984
Item Unit Width	120
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205137229
Packaging GTIN PL4	06414900119863
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	540
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	10,054
Packaging Weight PL4	551,36
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Wall thickness_s1	54
Wall thickness_s2	74
Wall thickness s3	54
Z Measurement A	61
Z Measurement b	57
Z Measurement d	1 1/2

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+