


GF Malleable Fittings 340 - union taper seat, galvanized 1/4

1154394

- Union taper seat, ISO/EN U11
- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * Inside hexagon
- ** Version



About GF Malleable Fittings 340 - union taper seat, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 340 - union taper seat, galvanized 1/4

1154394



Product code

Item no EAN	7611205438081
Item no GF	770340202
Item no GTIN	07611205438081
Item no RSK	1260769
Item no VVS	004340402

Dimensions

Item Unit Height	28
Item Unit Length	31
Item Unit Weight	0,0833
Item Unit Width	42
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205238087
Packaging GTIN PL4	06414900240901
Packaging Height PL1	100
Packaging Height PL4	508
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	60
Packaging Quantity PL4	4320
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	5,118
Packaging Weight PL4	379,856
Packaging Width PL1	190

Packaging Width PL4	800
---------------------	-----

Measurements

Wall thickness_s1	19
-------------------	----

Wall thickness_s2	28
-------------------	----

Wall thickness_s3	*10
-------------------	-----

Z Measurement a	42
-----------------	----

Z Measurement a	42
-----------------	----

Z Measurement d	1/4
-----------------	-----

z1	22
----	----

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com