Product data sheet





GF Malleable Fittings 344 - union taper seat, black 1/2

1154456

- Union taper seat

- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.





About GF Malleable Fittings 344 - union taper seat, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 344 - union taper seat, black 1/2

1154456





Product code

Item no EAN	7611205339456
Item no GF	770344104
Item no GTIN	07611205339456
Item no RSK	1260908
Item no VVS	004344104

Dimensions

Item Unit Height	41
Item Unit Length	45
Item Unit Weight	0,263
Item Unit Width	85
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205539450
Packaging GTIN PL2	07611205139452
Packaging GTIN PL4	06414900119474
Packaging Height PL1	41
Packaging Height PL2	200
Packaging Height PL4	534
Packaging Length PL1	135
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	50
Packaging Quantity PL4	1800
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00293355
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,51264
Packaging Weight PL1	2,638
Packaging Weight PL2	13,29
Packaging Weight PL4	503,44
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Wall thickness_s1	26
Wall thickness_s2	39
Wall thickness s3	23
Z Measurement b	85
Z Measurement d	1/2

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+