Product data sheet




GF Malleable Fittings 342a - union, spherical seat/taper seat Bronze to Bronze, galvanized 1/2

1154476

- Union, spherical seat/taper seat Bronze to Bronze, ISO/ENU11

- Torque and notes for installation please find in "Technical Product Notes".
- Not suitable for drinking water installation!
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.



About GF Malleable Fittings 342a - union, spherical seat/taper seat Bronze to Bronze, galvanized

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 342a - union, spherical seat/taper seat Bronze to Bronze, galvanized 1/2

1154476



Product code

Item no EAN	7611205439170
Item no GF	770345204
Item no GTIN	07611205439170
Item no RSK	1260893

Dimensions

Item Unit Height	44
Item Unit Length	48
Item Unit Weight	0,229
Item Unit Width	48
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205239176
Packaging GTIN PL4	06414900240611
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	70
Packaging Quantity PL4	3780
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	16,258

Packaging Weight PL4	886,376
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Wall thickness_s1	26
Wall thickness_s2	44
Wall thickness s3	26
Z Measurement A	48
Z Measurement d	1/2
z1	22

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+