


GF Malleable Fittings union bush flat seat 370 2 1/2 G

1154524

- Union bush flat seat
- * Is usually not supplied as a separate piece.
- ** Version



About GF Malleable Fittings union bush flat seat 370

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings union bush flat seat 370 2 1/2 G

1154524



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205442774
Item no GF	770370210
Item no GTIN	07611205442774
Item no RSK	1260976
Item no VVS	004370413

Dimensions

Item Unit Height	76
Item Unit Length	76
Item Unit Weight	0,6652
Item Unit Width	41
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205242770
Packaging GTIN PL4	06414900240253
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	30
Packaging Quantity PL4	810
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984
Packaging Weight PL1	20,376

Packaging Weight PL4	558,812
Packaging Width PL1	255
Packaging Width PL4	800

Measurements

Wall thickness_s	85
Z	14

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb