

GF Malleable Fittings union end reducer flat seat 372 1 - 3/4 G

1154576

- Union end flat seat, reducing
- 'G' refers to the thread size G of the union nut 374, which can be combined with the union end.



About GF Malleable Fittings union end reducer flat seat 372

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings union end reducer flat seat 372 1 - 3/4 G

1154576



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205444310
Item no GF	770372215
Item no GTIN	07611205444310
Item no RSK	1261032
Item no VVS	004372443

Dimensions

Item Unit Height	44
Item Unit Length	44
Item Unit Weight	0,093
Item Unit Width	25
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205244316
Packaging GTIN PL4	06414900240079
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	120
Packaging Quantity PL4	6480
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	11,374

Packaging Weight PL4	622,64
Packaging Width PL1	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb