Product data sheet




GF Malleable Fittings 526 - extension tube, galvanized 1 80

1154751

- Extension tube

- * Due to overall fitting length, the length of the external thread does not comply with the standard.



About GF Malleable Fittings 526 - extension tube, galvanized

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 526 - extension tube, galvanized 1 80

1154751



Product code

Item no EAN	7611205452957
Item no GF	770526234
Item no GTIN	07611205452957
Item no RSK	1363774
Item no VVS	004526488

Dimensions

Item Unit Height	46
Item Unit Length	46
Item Unit Weight	0,266
Item Unit Width	80
Item_UOM	pce

Measurements

LENGTH_L	80
Z Measurement A	80
Z Measurement d	1
Z	63

Packaging

Packaging GTIN PL1	07611205652951
Packaging GTIN PL2	07611205252953
Packaging GTIN PL4	06414900239257
Packaging Height PL1	46
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	300
Packaging Length PL2	260

Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	40
Packaging Quantity PL4	2160
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,007314
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	2,67
Packaging Weight PL2	10,78
Packaging Weight PL4	607,12
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+