


GF Malleable Fittings socket 529a 3/8 STA B

1154754

- Socket, internal and external thread, ISO/EN M4
- 'ST' these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations
- Steel parts are hexagonal instead of beaded.



About GF Malleable Fittings socket 529a

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings socket 529a 3/8 STA B

1154754



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205353407
Item no GF	770529103
Item no GTIN	07611205353407
Item no RSK	1311620

Dimensions

Item Unit Height	27
Item Unit Length	27
Item Unit Weight	0,0448
Item Unit Width	35
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205553401
Packaging GTIN PL2	07611205153403
Packaging GTIN PL4	06414900071819
Packaging Height PL1	27
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	135
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	100
Packaging Quantity PL4	7200
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00193185
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,4526575
Packaging Weight PL2	4,646575
Packaging Weight PL4	359,5534
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800
Measurements	
Wall thickness_s	22
Z	25

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb