

GF Malleable Fittings FIG. 330 gasket C-4430 2 78x60x3

1154905

About GF Malleable Fittings FIG. 330 gasket C-4430 2

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings FIG. 330 gasket C-4430 2 78x60x3

1154905

Product code

Item no EAN	7611205463021
Item no GF	770971402
Item no GTIN	07611205463021

Dimensions

Item Unit Height	78
Item Unit Length	60
Item Unit Weight	0,005
Item Unit Width	3
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205263027
Packaging GTIN PL4	06414900238762
Packaging Height PL1	195
Packaging Height PL4	729
Packaging Length PL1	255
Packaging Length PL4	1200
Packaging Quantity PL1	200
Packaging Quantity PL4	10800
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,009199125
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,254
Packaging Weight PL4	20,27
Packaging Width PL1	185
Packaging Width PL4	800

Status

Until stocks last	Until stocks last
-------------------	-------------------

Technical documents
[Download documents here](#) 
www.uponor.com/en-gb