


GF JRGURED pressure reducing valve 1330 6 bar DN15

1157285

- Description: pressure gauge connection on both sides, gunmetal filter cup, with unions
- Temperature: max. 70°C
- Nominal pressure: PN25
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar), adjustable on site 600 - 1000 kPa (6 - 10 bar)
- Connection: male thread



About GF JRGURED pressure reducing valve 1330 6 bar

Specification

- Dimension range DN15 – DN100
- Three different pressure ranges (0.5 – 2bar, 2 – 6bar, and 6 – 10 bar) with factory settings (e.g. 2, 4 and 6 bar)

Application

- House water inlet
- Potable water and oil-free compressed air
- Inlet modulation for machines and appliances

GF JRGURED pressure reducing valve 1330 6 bar DN15

1157285



Measurements

Cylindric thread G2	3/4
Female thread Rp3	1/8
Length (l1)	130
Length (l2)	25
MALE THREAD R1	1/2
Z Measurement d	15
Z Measurement d4	53
Z Measurement h1	34
Z Measurement h2	79
Z	40

Status

Item Available From date 2026-05-01

Product code

Item no EAN	7613263116321
Item no GF	350740161
Item no GTIN	07613263116321

Dimensions

Item Unit Height	108
Item Unit Length	130
Item Unit Weight	0,78
Item Unit Width	62
Item_UOM	pce

Packaging

Packaging GTIN PL1	07613263116321
Packaging Height PL1	70
Packaging Length PL1	150
Packaging Quantity PL1	1

Packaging Type PL1	Base_Box
Packaging Volume PL1	0,000945
Packaging Weight PL1	0,8
Packaging Width PL1	90

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com