

GF JRGURED pressure reducing valve 1330 6bar DN25

1157299

- Description: pressure gauge connection on both sides, gunmetal filter cup, with unions
- Temperature: max. 70°C
- Nominal pressure: PN25
- Material: gunmetal, stainless steel, EPDM, plastic
- Factory setting: 600 kPa (6 bar), adjustable on site 600 - 1000 kPa (6 - 10 bar)
- Connection: male thread



About GF JRGURED pressure reducing valve 1330 6bar

Specification

- Dimension range DN15 – DN100
- Three different pressure ranges (0.5 – 2bar, 2 – 6bar, and 6 – 10 bar) with factory settings (e.g. 2, 4 and 6 bar)

Application

- House water inlet
- Potable water and oil-free compressed air
- Inlet modulation for machines and appliances

GF JRGURED pressure reducing valve 1330 6bar DN25

1157299



Status

Item Available From date

2025-07-17

Product code

Item no EAN	7613263116406
Item no GF	350740361
Item no GTIN	07613263116406

Dimensions

Item Unit Height	145
Item Unit Length	167
Item Unit Weight	1,8
Item Unit Width	70
Item_UOM	pce

Measurements

Length (l1)	167
Length (l2)	34
Z Measurement h1	55
Z Measurement h2	90
Z	50

Packaging

Packaging GTIN PL1	07613263116406
Packaging Height PL1	80
Packaging Length PL1	205
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,001804
Packaging Weight PL1	1,9
Packaging Width PL1	110

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb