


## GF JRG Sanipex MT adapter for push connection sudoFIT d16-15

**1157570**

- Description: for stainless steel / copper pipes
- Temperature: max. 90°C
- Material: gunmetal, PPSU
- Connection: push-in system sudoFIT
- Permissible tubes can be found in the installation instructions for the fitter's toolkit JRG code 8130.000
- Approved for the following pipe types and systems: (For other approvals, please contact our technical customer service).
- Stainless steel pipes / PN16 / Ø 15, 18, 22, 28, 35, 42, 54 / Mapress / Optipress, Sanpress /inoxPRES
- Copper pipes / PN10 / Ø 12, 15, 18, 22, 28, 35, 42, 54 / WICU, KME / SANCO, Wieland-Werke /SANCO, KME



### About GF JRG Sanipex MT adapter for push connection sudoFIT

#### Specification

- Wide product range
- Gunmetal body

#### Application

Potable water installations

#### Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## GF JRG Sanipex MT adapter for push connection sudoFIT d16-15

1157570



### Measurements

Inner_diameter_di	16
Length (l1)	62
Z Measurement d2	15
z1	21

### Product code

Item no EAN	7613263005373
Item no GF	351060501
Item no GTIN	07613263005373
Item no LVI	1749105
Item no RSK	1880165

### Dimensions

Item Unit Height	28
Item Unit Length	67
Item Unit Weight	0,075
Item Unit Width	28
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900235594
Packaging Height PL1	28
Packaging Length PL1	67
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000052136
Packaging Weight PL1	0,085
Packaging Width PL1	28

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavillion  
WD18 8GA, Watford  
UK

T +44 (0)1923 381212

E  
customerservice.uk.bfs@georgfi  
scher.com