


GF JRG Sanipex MT adapter for push connection sudoFIT d20-22

1157571

- Description: for stainless steel / copper pipes
- Temperature: max. 90°C
- Material: gunmetal, PPSU
- Connection: push-in system sudoFIT
- Permissible tubes can be found in the installation instructions for the fitter's toolkit JRG code 8130.000
- Approved for the following pipe types and systems: (For other approvals, please contact our technical customer service).
- Stainless steel pipes / PN16 / Ø 15, 18, 22, 28, 35, 42, 54 / Mapress / Optipress, Sanpress /inoxPRES
- Copper pipes / PN10 / Ø 12, 15, 18, 22, 28, 35, 42, 54 / WICU, KME / SANCO, Wieland-Werke /SANCO, KME



About GF JRG Sanipex MT adapter for push connection sudoFIT

Specification

- Wide product range
- Gunmetal body

Application

Potable water installations

Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF JRG Sanipex MT adapter for push connection sudoFIT d20-22

1157571



Measurements

Inner_diameter_di	20
Length (l1)	76
Z Measurement d2	18
z1	24

Product code

Item no EAN	7613263005366
Item no GF	351060511
Item no GTIN	07613263005366
Item no LVI	1749106
Item no RSK	1880166

Dimensions

Item Unit Height	34
Item Unit Length	82
Item Unit Weight	0,125
Item Unit Width	34
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900209076
Packaging Height PL1	34
Packaging Length PL1	82
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000094214
Packaging Weight PL1	0,135
Packaging Width PL1	34

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com