


GF JRG Sanipex MT adapter for push connection sudoFIT d26-22

1157573

- Description: for stainless steel / copper pipes
- Temperature: max. 90°C
- Material: gunmetal, PPSU
- Connection: push-in system sudoFIT
- Permissible tubes can be found in the installation instructions for the fitter's toolkit JRG code 8130.000
- Approved for the following pipe types and systems: (For other approvals, please contact our technical customer service).
- Stainless steel pipes / PN16 / Ø 15, 18, 22, 28, 35, 42, 54 / Mapress / Optipress, Sanpress /inoxPRES
- Copper pipes / PN10 / Ø 12, 15, 18, 22, 28, 35, 42, 54 / WICU, KME / SANCO, Wieland-Werke /SANCO, KME



About GF JRG Sanipex MT adapter for push connection sudoFIT

Specification

- Wide product range
- Gunmetal body

Application

Potable water installations

Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF JRG Sanipex MT adapter for push conection sudoFIT d26-22

1157573



Measurements

Inner_diameter_di	26
Length (l1)	75
Z Measurement d2	22
z1	15

Product code

Item no EAN	7613263005342
Item no GF	351060521
Item no GTIN	07613263005342
Item no LVI	1749108
Item no RSK	1880167

Dimensions

Item Unit Height	43
Item Unit Length	81
Item Unit Weight	0,14
Item Unit Width	43
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900209052
Packaging Height PL1	43
Packaging Length PL1	80
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,00014792
Packaging Weight PL1	0,15
Packaging Width PL1	43

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com