


GF JRG Sanipex MT adapter for push connection sudoFIT d32-28

1157574

- Description: for stainless steel / copper pipes
- Temperature: max. 90°C
- Material: gunmetal, PPSU
- Connection: push-in system sudoFIT
- Permissible tubes can be found in the installation instructions for the fitter's toolkit JRG code 8130.000
- Approved for the following pipe types and systems: (For other approvals, please contact our technical customer service).
- Stainless steel pipes / PN16 / Ø 15, 18, 22, 28, 35, 42, 54 / Mapress / Optipress, Sanpress /inoxPRES
- Copper pipes / PN10 / Ø 12, 15, 18, 22, 28, 35, 42, 54 / WICU, KME / SANCO, Wieland-Werke /SANCO, KME



About GF JRG Sanipex MT adapter for push connection sudoFIT

Specification

- Wide product range
- Gunmetal body

Application

Potable water installations

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF JRG Sanipex MT adapter for push connection sudoFIT d32-28

1157574



Measurements

Inner_diameter_di	32
Length (l1)	93
Z Measurement d2	28
z1	14

Product code

Item no EAN	7613263005335
Item no GF	351060531
Item no GTIN	07613263005335
Item no LVI	1749109
Item no RSK	1880168

Dimensions

Item Unit Height	53
Item Unit Length	100
Item Unit Weight	0,245
Item Unit Width	53
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900235631
Packaging Height PL1	53
Packaging Length PL1	100
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,0002809
Packaging Weight PL1	0,255
Packaging Width PL1	53

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com