

GF JRG Sanipex inlay with IG MT 26-1/2

1158814

- threaded connection insert
- brass construction
- enables integration with threaded fittings
- suitable for plumbing installations



About GF JRG Sanipex inlay with IG MT

Specification

- The pipe-in-pipe technology enables the pipes to be installed directly into the concrete.
- The water-carrying inner pipe of dimensions d12 and d16 – if it has been installed in the protective conduit – can be replaced without prising open the floor coverings and wall plates if damaged.

Application

- Application area Cold and hot water, HVAC, compressed air, greywater
-
- Installation
- above all, flush-mounted pipes from distributors to the
- location of the taps in pipe-in-pipe technology

Certification

- 3,1
- SVGW
- KIWA
- ÖVGW

GF JRG Sanipex inlay with IG MT 26-1/2

1158814

**Product code**

Item no EAN	7613263089076
Item no GF	358300050
Item no GTIN	07613263089076

Dimensions

Item Unit Height	32
Item Unit Length	39
Item Unit Weight	0,06
Item Unit Width	32
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900068079
Packaging Height PL1	178
Packaging Length PL1	242
Packaging Quantity PL1	100
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0075383
Packaging Weight PL1	6,125
Packaging Width PL1	175

Technical documents[Download documents here](#) **Uponor UK**

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb