Product data sheet



GF Hycleen power supply and communication cable, push-pull 3m

1162885

- 30V DC power supply for Hycleen Balance / Flush
- Circulation control valves, max. 100m cable lengths and 10x valves
- Consisting of: 1.5m power cable



About GF Hycleen power supply and communication cable, push-pull

Specification

- 30 V DC power supplies for Hycleen Balance and Flush systems
- Communication and extension cables with M8 push-pull connectors
- BMS connection via Modbus RTU
- Temperature sensors PT1000 and 4–20 mA sensor adapters
- Flow sensors and drain surveillance sensors
- Insulation shells made of EPP for DN15 and DN20 valves
- Sensor extension cables and spare sensor components

Application

- Power supply and electrical connection of Hycleen Balance and Flush systems
- Communication and bus extension between Hycleen components
- Integration with building management systems (BMS)
- Temperature, flow, and leakage monitoring in drinking water installations
- Protection, insulation and installation support of hygiene flushing valves

GF Hycleen power supply and communication cable, push-pull 3m

1162885



Status

Item Available From date	2026-03-01

Product code

Item no EAN	6414900451932
Item no GF	351112152
Item no GTIN	06414900451932
Item no LVI	2022407

Dimensions

Item Unit Height	18
Item Unit Length	260
Item Unit Weight	0,108
Item Unit Width	260
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900451949
Packaging Height PL1	18
Packaging Length PL1	260
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,0012168
Packaging Weight PL1	0,1100
Packaging Width PL1	260

Measurements

Z Measurement d1	M8

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+