

GF Hycleen power supply and communication cable push-pull 5m

1162886

- 30V DC power supply for Hycleen Balance / Flush
- Circulation control valves, max. 100m cable lengths and 10x valves
- Consisting of: 1.5m power cable



About GF Hycleen power supply and communication cable push-pull

Specification

- 30 V DC power supplies for Hycleen Balance and Flush systems
- Communication and extension cables with M8 push-pull connectors
- BMS connection via Modbus RTU
- Temperature sensors PT1000 and 4–20 mA sensor adapters
- Flow sensors and drain surveillance sensors
- Insulation shells made of EPP for DN15 and DN20 valves
- Sensor extension cables and spare sensor components

Application

- Power supply and electrical connection of Hycleen Balance and Flush systems
- Communication and bus extension between Hycleen components
- Integration with building management systems (BMS)
- Temperature, flow, and leakage monitoring in drinking water installations
- Protection, insulation and installation support of hygiene flushing valves

GF Hycleen power supply and communication cable push-pull 5m

1162886



Status

Item Available From date 2026-03-01

Product code

Item no EAN	6414900451956
Item no GF	351112153
Item no GTIN	06414900451956
Item no LVI	2022408

Dimensions

Item Unit Height	20
Item Unit Length	260
Item Unit Weight	0,18
Item Unit Width	260
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900451963
Packaging Height PL1	20
Packaging Length PL1	260
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,001352
Packaging Weight PL1	0,1820
Packaging Width PL1	260

Technical documents

[Download documents here](#)

W316 607, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb