


Uponor Vario S manifold flowmeter gen.2 0-5 l/min.

1184878

- Flowmeter for stainless steel manifold Vario S
- Replacement for item 1087608
- 0-5 l/min.
- With mechanical stop during opening/closing position



About Uponor Vario S manifold flowmeter gen.2

Specification


- Made of stainless steel, with integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill & drain points in supply/return
- Loop connection G3/4" Eurocone c-c 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- For use with with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold flowmeter gen.2 0-5 l/min.

1184878



Measurements

Cylindric_thread_G	1/2
LENGTH_L	97
Length (l1)	51
Outer Diameter_do	31

Status

Item Available From date	2025-12-10
--------------------------	------------

Product code

Item no EAN	6414900137157
Item no GTIN	06414900137157
Item no LVI	2022367

Dimensions

Item Unit Height	25
Item Unit Length	100
Item Unit Weight	0,07
Item Unit Width	25
Item_UOM	pce

Technical data

Recycling Text Block PL1	corrugated cardboard / cartone
--------------------------	--------------------------------

Packaging

Packaging GTIN PL1	06414900619202
Packaging Height PL1	60
Packaging Length PL1	155
Packaging Material (number) PL1	20
Packaging Material PL1	corrugated cardboard / cartone
Packaging Material (short) PL1	PAP_C
Packaging Quantity PL1	10
Packaging Type PL1	Base_Box

Packaging Volume PL1	0,000744
Packaging Weight PL1	0,739
Packaging Width PL1	80

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb