

References

## Würth Logistics Centre, Lithuania



### Uponor involvement

✓ 18 km PE-Xa d20 | 23 Q&E manifolds | 2,4 km Ecoflex Thermo Twin

## Würth Logistics Centre, Lithuania

Würth Logistics Centre is an exclusive build-to-suit project incorporating renewable energy sources.

Würth Logistics Centre: an exclusive build-to-suit project incorporating renewable energy sources

### Project Facts:

Location

Ukmergė district municipality, Vilnius  
county, Lithuania

Completion

2014

Building Type

Industrial buildings

Product systems

Radiant Heating & Cooling, Local  
Heat Distribution

Address

Jačionys village, Pivonija  
Neighbourhood, Ukmergė District  
Municipality,

Website

<http://www.wurth.lt/>

Project Type

New building

The low-parameter, surface heating/cooling solutions deployed in this project are much more efficient than conventional heating systems. As a result, the desired temperature can be maintained in designated parts of the building instead of overheating zones at the top, as is the case with convection heating. System integration with efficient geothermal sources ensures very low operating costs, and creates maximum comfort for people working in the building.

High demand and market potential for logistics buildings was recorded in Lithuania in the years 2011–2014. Therefore, a number of construction projects were implemented in that period, including build-to-rent logistics centres and build-to-suit buildings catering to highly specific client requirements.

The construction of the Würth Logistics Centre began in spring 2013 and combines two different zones: industrial warehousing and administration. The warehousing zone is an open 13-metre high space. The first floor of the centre's administrative section contains a lobby, a shop, a café-canteen with a kitchen, a meeting room and technical premises. Administrative rooms and a meeting hall are located on the second floor.

The combination of different purposes in one building dictated the need for exclusive engineering solutions. Moreover, the client requested an energy-efficient solution.

The plot of land on which the logistics building is situated has 18 geothermal wells and Stiebel Eltron heating pumps with a total heating capacity of 138 kW. The pumps take heating from vertical geothermal probes.

The entire centre has Uponor radiant heating/cooling solutions installed. The administrative zone has a fitted PE-Xa d20 underfloor heating system with wired room controls (the parameter of the heat-transfer medium is 45 / 40 °C). The industrial and warehousing zone has an industrial underfloor heating system whose temperature is controlled via heat-transfer medium. The system maintains heating in the range of 25–35 °C.

The object has about 5,000 m<sup>2</sup> of heated surface in total, with approx. 18 km of pipes and 23 Q&E modular collectors fitted under the floor. These collectors stand out from other similar products due to connectors that are free of rubber sealants and sturdier than a pipe, and due to the heat-transfer medium which is fed via pre-insulated Uponor Thermo Twin pipe systems.

In industrial buildings, large heating systems are usually mounted next to the ceiling. However, solutions such as these affect construction elements of the building and the reliability of connecting points. In order to avoid such issues, Uponor developed the Thermo Twin pipe systems. These systems are mounted in the ground: they are more reliable, fewer pipes are needed and they are faster to install and implement.

Due to selection of the right heating system, the logistics centre building can also be cooled to 16-19 °C in summer.

The centre is built next to Vilnius-Panevėžys motorway. Its functional zones are clearly distinguished by bright colours on the outside of the building: the warehousing zone is grey and the administrative zone is red, with extensive use of tinted glass. This colouring mirrors that of the Würth logo.

Watch a video of the building process: <https://www.youtube.com/watch?v=2PvsxIEmUml>

## Würth Logistics Centre, Lithuania





+GF+