

Ecoflex potable PEX plus accessories

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

Ambient temperature min. [F] -40 °f
Ambient temperature max. [F] 122 °f

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



| Part name | Part no. | Material group | Operating voltage [V] | Output rating at 24VAC [A] | Subcomponent Material |
|---------------------------------|----------|---|-----------------------|----------------------------|---|
| Heat-trace Power Terminal Block | 5992000 | Body: polyamide; conductors: nickel-coated brass | 275 | 16 | - |
| Heat-trace End Seal, SF-E | 5993000 | - | 275 | 16 | Body: polyamide; conductors: nickel-coated brass |
| Heat-trace Tee Splice, SF-T | 5994000 | - | 275 | 16 | Body: polyamide; conductors: nickel-coated brass |

| Part name | Part no. | Codes | Standards | Listings |
|--------------------------------------|----------|-------|-----------|--------------------|
| Ecoflex potable PEX plus accessories | All | - | - | IECEX SIR 11.0136U |

| Installation | Related applications |
|---|---|
| Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual. | Pre-Insulated Pipe Systems Permafrost Prevention Systems PEX-a Plumbing Systems |

Notes

Power cable:
3c x 2.5mm2 (supplied by others)
Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

| Footnotes | Contact information |
|-----------|--|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |