

# Ecoflex potable PEX plus accessories

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material Body: polyamide; conductors: nickel-coated brass

## Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Part name	Part no.	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	1.27
Heat-trace End Seal, SF-E	5993000	0.05
Heat-trace Tee Splice, SF-T	5994000	1.18

## Installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

## Related applications

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- PEX-a Plumbing Systems

## Codes

## Standards

## Listings

-	-	IECEX SIR 11.0136U
---	---	--------------------

## Notes

Power cable:  
3c x 2.5mm<sup>2</sup> (supplied by others)  
Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

## Footnotes

## Contact information

-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p>	<p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>
---	--	--