

Ecoflex potable PEX plus accessories

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Body: polyamide; conductors: nickel-coated brass
Subcomponent Material	Body: polyamide; conductors: nickel-coated brass
Ambient temperature min. [F]	-40 °f
Ambient temperature max. [F]	122 °f

Product Information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Part name	Part no.	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	1.27
Heat-trace End Seal, SF-E	5993000	0.05
Heat-trace Tee Splice, SF-T	5994000	1.18

Part name	Part no.	Codes	Standards	Listings
Ecoflex potable PEX plus accessories	All	-	-	IECEX SIR 11.0136U

Installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- PEX-a Plumbing Systems

Notes

Power cable:
 3c x 2.5mm2 (supplied by others)
 Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

Footnotes

Contact information

Uponor Inc.
 5925 148th Street West
 Apple Valley, MN 55124
 T 800.321.4739
 F 952.891.2008

Uponor Ltd.
 6510 Kennedy Road
 Mississauga, ON L5T 2X4
 T 888.594.7726
 F 800.638.9517