Ecoflex potable PEX plus accessories

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Subcomponent Material
Ambient temperature min. [F] -40 °f
Ambient temperature max. [F] 482 °f

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



	Part name	Part no.	Weight per UOM [lbs/UOM]
	Heat-trace Power Terminal Block	5992000	0.3
✔	Heat-trace End Seal	5993000	0.05
	Heat-trace Tee Splice	5994000	0.3

Part name	Part no.	Codes	Standards	Listings
Ecoflex potable PEX plus accessories	All	-	-	IECEx SIR 11.0136U

Installation

Simply cut back one wire $\frac{1}{4}$" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

Pre-Insulated Pipe Systems

Permafrost Prevention Systems

PEX-a Plumbing Systems

Notes

Voltage Range 220 to 277

Voltage Range 220 to 277.

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved