

## Wirsbo hePEX straight lengths

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material PEX

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar)

200 °F (93 °C) at 80 psi (5.5 bar)

## Product information and application use

Wirsbo hePEX™ tubing is used for closed-loop heating and cooling applications, including radiant and hydronic distribution. Wirsbo hePEX tubing has an EVOH oxygen diffusion barrier that meets German DIN 4726/9. A polyethylene layer extruded over the EVOH barrier protects tubing from site abuse and moisture saturation.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Installation Related applications

Use ProPEX® fittings for pipe sizes to 3\*.1 Use WIPEX™ fittings for 3½2\* and 4\* pipe. Refer to the Uponor Complete Design Assistance Manual (CDAM) or the Uponor Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems
Chilled water distribution

Hot water distribution

 Footnotes
 Contact information

 Uponor Inc.
 Uponor Ltd.

 5925 148th Street West
 6510 Kennedy Road

 Apple Valley, MN 55124
 Mississauga, ON L5T 2X4

 T 800.321.4739
 T 888.594.7726

 F 952.891.2008
 F 800.638.9517