
# Stainless-steel manifold assembly, 1 1/4" with flow meter

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

## Technical data

| | |
|---|---|
| Material | Stainless Steel |
| Subcomponent Material | Manifold Components:<br>Brass CW614N-UNI EN12164, CW617N-UNI EN12165 |
| Manifold size | 1.25 inch |
| Loop Cv | 1.1 Cv |
| End type 1 | ISO 228-G 1-1/4" |
| End type 2 | ISO 228-G 3/4" |
| Temp/pressure ratings | 68 °F (20 °C) at 145 psi (10 bar)<br>158 °F (70 °C) at 87 psi (6 bar)<br>194 °F (90 °C) at 44 psi (3 bar) |
| Max. fluid flow rate | 21 gpm |
| Prop 65 label required? | Yes |




## Product information and application use

The 1¼" Stainless-steel Manifold Assembly with flow meter comes fully assembled and ready for installation. Use the included flow meters located on the supply manifold to balance the loops across the manifold. The return manifold comes equipped with isolation valves for easy loop isolation. For multiple zoning on the manifold, the black caps are removed and replaced with Uponor Thermal Actuators. The manifold body ends have R32 union connections and the loop outlets have R20 male threads. The included manifold supply and return ball valves come with an R32 x 1" NPT or R32 x 1¼" NPT connection. Note: The 1¼" manifolds with 2 through 7 loops are strategically designed with 1" NPT ball valves to avoid adding extra costs while maintaining the maximum flow of the manifold assembly.

| | Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | Weight per UOM [lbs/UOM] |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 2 loops | A2720202 | 10.933 | 14.46 | 3.542 | 1.969 | 5.425 | 1.75 | 2.25 | 6.342 | 9.22 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 3 loops | A2720302 | 12.902 | 14.46 | 3.542 | 1.969 | 5.425 | 1.75 | 2.25 | 8.249 | 10.12 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 4 loops | A2720402 | 14.87 | 14.46 | 3.542 | 1.969 | 5.425 | 1.75 | 2.25 | 10.211 | 11.02 |
| ✔ | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 5 loops | A2720502 | 16.839 | 14.46 | 3.541 | 1.969 | 5.425 | 1.75 | 2.25 | 12.131 | 11.92 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 6 loops | A2720602 | 19.066 | 14.47 | 3.456 | 1.969 | 5.504 | 1.75 | 2.25 | 14.175 | 12.82 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 7 loops | A2720702 | 20.776 | 14.46 | 3.542 | 1.969 | 5.425 | 1.75 | 2.25 | 16.156 | 13.72 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 8 loops | A2720802 | 23.095 | 14.46 | 3.439 | 1.969 | 5.776 | 1.75 | 2.25 | 18.262 | 15.32 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 10 loops | A2721002 | 27.291 | 14.47 | 3.415 | 1.969 | 5.855 | 1.75 | 2.25 | 22.189 | 17.12 |
| | Stainless-steel Manifold Assembly, 1 1/4" with flow meter, B&I, ball valve, 12 loops | A2721202 | 31.228 | 14.47 | 3.415 | 1.969 | 5.855 | 1.75 | 2.25 | 26.106 | 18.92 |

## Installation

The 1¼" Stainless-steel Manifolds are fully assembled and ready for installation. Manifold assembly comes with mounting brackets, isolation valves, balancing valves, fill/purge ports, air vents, ball valves, temperature gauges and end caps. Manifold adapters and fittings are sold separately. For further information, refer to the Uponor Stainless-steel Manifold Installation Guide.

## Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

AquaSAFE™ Fire Safety Systems

## Footnotes

-

## Contact information


Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517


© 2026 Uponor North America. All Rights Reserved