Two-wire thermal actuators for Stainless-steel Manifolds

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



	Part name	Part no.	A [inch]	B [inch]	C [inch]	Current draw max. [A]	Operating voltage AC [VAC]	Weight per UOM [lbs/UOM]
✔	Two-wire Thermal Actuator for Stainless-steel Manifolds	A3030524	2.5	1.56	1.56	0.083	24	0.25

Part name	Part no.	Codes	Standards	Listings
Two-wire thermal actuators for Stainless-steel Manifolds	A3030524	-	Class II wiring	-

Installation

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Notes

Time to Open/Close:
3 to 5 minutes

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved