υροποι

Powered zone controllers

Project Information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes Product information and application use

The Uponor Powered Four- and Six-zone Controllers feature transformers for low-voltage operations and relays to operate line-voltage controls. Fully fuse protected, they also include an isolated switch and built-in domestic hot water (DHW) priority switch. The indicator lights show full functionality of the products wired to the Powered Zone Controllers. The green light indicates power is connected. When the thermostat calls for heat, both the appropriate zone valve and yellow indicator light activate. When the zone valve is fully open, the end switch relay and red indicator light activate. A 3-amp delay fuse protects the Powered Four-zone Controller. A 7-amp delay fuse protects the Powered Six-zone Controller.

All



UL

Part name		Part no.	Current draw max. [A]	Operating voltage AC [VAC]
Powered Four-	-zone Controller	A3080404	3	120
Powered Six-z	one Controller	A3080406	7	120
Part name	Part no.	Codes	Standards	Listings

Istallation Related applications	
	Radiant Heating and Cooling Systems
For installation instructions, refer to the Uponor Powered Zone Controllers Instruction Sheet	Permafrost Protection Systems

Turf Conditioning Systems

Notes

Maximum Zones: 4 with priority

Powered zone controllers

Maximum Zones: 6 with priority

Footnotes	Contact information		
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	