υροποι

Heat-only thermostats with touchscreen

-

Prop 65 label required? Yes Product information and application use

The Uponor Heat-only Thermostat with Touchscreen (A3100101) is a simple, non-programmable thermostat designed to sense room air temperature using operative temperature and/or floor temperature via an optional floor sensor (A9010599).



Part name Part n	o. A [inch]	B [inch]	C [inch]	draw max. [A]	voltage AC [VAC]	rating at 24VAC [A]	Weight per UOM [lbs/UOM]
Heat-only Thermostat with Touchscreen A310	0101 5.394	3.227	0.801	0.042	24	1.3	0.24
Slab Sensor, 10k A901		-	-	-	-	-	0.3

Installation

Install the thermostat on an interior wall of the desired zone approximately 5 feet above the floor. Do not mount the thermostat on a location that may be affected by localized heat sources or cold drafts. It may be necessary to install a draft barrier behind the thermostat to prevent air from blowing through the wiring hole which can affect the thermostat's built-in sensor. Refer to the Uponor Heat-only Thermostat with Touchscreen Installation and Operation Manual for more information.

Related applications

Radiant heating systems

Notes

Floor sensor: 10K, J-curve thermistor

Ambient conditions: 10% to 90% humidity (non-condensing) Sensor type: 10k J-curve Tolerance: +/- 1% at 77°F (25°C) Wire type: 22 gauge IP68 continuous immersion 3m /10 ft

Uponor Ltd.
0 Kennedy Road
sauga, ON L5T 2X4
888.594.7726
800.638.9517