

HDPE valveless manifolds

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	HDPE
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 120 °F (49 °C) at 100 psi (6.9 bar) 140 °F (60 °C) at 80 psi (5.5 bar) 100 °F (38 °C) at 125 psi (8.6 bar)
Prop 65 label required?	Yes

Product information and application use

Uponor offers the multiple-outlet HDPE Valveless Manifolds for applications with greater flow requirements (larger than 5,000 square feet). Manufactured with grade 303 stainless steel ProPEX® fittings (3/4" or 1") hydraulically pressed onto the outlet nipples, these manifolds are maintenance-free and suitable for direct burial. The HDPE Valveless Manifolds come with standard 12" on-center (o.c.) outlet spacing.

This product is made to order, please contact [customer service](#) for lead time.



Part name	Part no.	Codes	Standards	Listings
HDPE valveless manifolds	All	NPC of Canada NSPC	ASTM F1960 CSA B137.5 NSF-61 ASTM D3350 NSF-14 CGSB 41-GP-25M	NSF 14- and 61-certified PPI PE-3408

Installation

Connect HDPE tubing through fusion welding. Connect PEX tubing to outlets via ProPEX connection method. For additional information, refer to the Radiant Floor Heating Installation Handbook.

Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

140°F at 80 psi (60°C at 5.5 bar)
120°F at 100 psi (49°C at 6.9 bar)
100°F at 125 psi (38°C at 8.6 bar)
73.4°F at 160 psi (23°C at 11 bar)
Maximum Recommended Flow Rates:
2" — 41 gpm; 3" — 116 gpm; 4"

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517