

# Uponor AquaPEX red straight lengths

## Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

## Product information and application use

Uponor AquaPEX® red tubing is an Engel-method, PEX-a pipe designed for hot potable-water distribution, but can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name	Part no.	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Bundle Diameter [in]	Bundle Length [in]	Weight per UOM [lbs/UOM]
1/2" Uponor AquaPEX Red, 20-ft. straight length, 500 ft. (25 per bundle)	F2930500	0.475	0.625	3.5	258	28
3/4" Uponor AquaPEX Red, 20-ft. straight length, 300 ft. (15 per bundle)	F2930750	0.671	0.875	4.5	258	31
1" Uponor AquaPEX Red, 20-ft. straight length, 200 ft. (10 per bundle)	F2921000	0.862	1.125	4	258	35

Part name	Part no.	Codes	Standards	Listings
Uponor AquaPEX red straight lengths	All	UPC IMC NBC of Canada IPC IBC IRC UMC NSPC UFGS NPC of Canada	ASTM E119 UL 263 ASTM F1960 ASTM E84 ASTM F2023 ASTM E814 ULC S115 CSA B214 CSA B137.5 NSF/ANSI 14 NSF/ANSI/CAN 61 ASTM F876 ASTM F877 ULC S102.2 ULC S101	cNSFus-pw IAPMO-ES ICC-ES-PMG CSA CCMC PPI TR-4 cQA us P321 UL U.P.Code BMEC

## Installation

Approved fitting system is ProPEX®1. Refer to the Uponor ProPEX Connections Instructional Guide, the Uponor Professional Plumbing Installation Guide or the Uponor Piping Pocket Guide for more information.

## Related applications

PEX-a Plumbing Systems

## Footnotes

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517