

# PEX stand-up brackets

## Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

## Technical data

|                         |         |
|-------------------------|---------|
| Material                | Plastic |
| Subcomponent Material   | PVC     |
| Prop 65 label required? | Yes     |

## Product information and application use

Use the PEX Stand-up Bracket in residential slab or commercial multi-floor construction. The brackets are available in either single-tube or five-tube configurations. The bracket supports up to 1" Uponor hePEX™ plus or Uponor AQUAPEX® tubing, or a 1" utility-grade, polyethylene sleeving.



| Part name                                     | Part no. | Weight per UOM [lbs/UOM] |
|---|----------|--------------------------|
| Single-tube PEX Stand-up Bracket for 1/2" PEX | F5801000 | 0.5                      |
| Five-tube PEX Stand-up Bracket for 1/2" PEX   | F5805000 | 1.1                      |

## Installation

Screw or nail the 3/4" fastening tab to the floor or concrete forms. Secure the brackets to the deck form. Then install the 1/2" PEX tubing in the brackets, either with the 1/2" PEX tubing alone or with the 1/2" PEX tubing sleeved inside corrugated polyethylene carrier tube. Wire the tube at the top of bracket to bracket at the wiring tab.

## Related applications

PEX-a Plumbing Systems  
Radiant Floor Heating and Cooling Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517