ProPEX lead-free (LF) brass commercial ball valve stem extension kits

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material Galvanized steel

Product information and application use

To help meet the stringent demands of commercial plumbing and hydronic distribution projects, Uponor is offering new ProPEX® ASTM F1960 lead-free (LF) brass ball valves in sizes from ½" to 2". The full-port ball valves feature a stainless-steel ball and stem for greater durability, longevity, and system performance.



	Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]
✔	2 3/8" Stem Extension Kit for 1/2" and 3/4" LFCSS Ball Valves	F6630001	3.3	1.02	1.02	2.82	0.39
	2 5/8" Stem Extension Kit for 1" and 1 1/4" LFCSS Ball Valves	F6630002	3.4	1.293	1.293	2.8	0.66
	2 5/8" Stem Extension Kit for 1 1/2" and 2" LFCSS Ball Valves	F6630003	3.57	1.369	1.369	2.88	0.77

Installation

Install valve and stem extension kit according to local building code. Do not dismantle. Refer to the Uponor Piping Pocket Guide or the Uponor Plumbing Design Assistance Manual (PDAM) for additional information.

Related applications

Hot water distribution

Hydronic heating and cooling systems

Hydronic Piping Systems

Hydronic Radiant Heating and Cooling Systems

PEX-a Plumbing Systems

Plumbing Systems

Pre-Insulated Pipe Systems

Radiant Heating and Cooling Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved