PEX-a pipe supports

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.

	Part name	Part no.	Material group	Subcomponent Material	Prop 65 label required?
✔	1/2" PEX-a Pipe Support, 9-ft. length	F7040500	Metal	Commercial-grade (Type B) galvanized steel	-
	3/4" PEX-a Pipe Support, 9-ft. length	F7040750	Metal	Commercial-grade (Type B) galvanized steel	No
	1" PEX-a Pipe Support, 9-ft. length	F7041000	Metal	Commercial-grade (Type B) galvanized steel	-
	1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	Metal	Commercial-grade (Type B) galvanized steel	-
	1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	Metal	Commercial-grade (Type B) galvanized steel	-
	2" PEX-a Pipe Support, 9-ft. length	F7042000	Metal	Commercial-grade (Type B) galvanized steel	-
	2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	Metal	Commercial-grade (Type B) galvanized steel	-
	PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX	Q7410510	Plastic	-	-
	3" PEX-a Pipe Support, 9-ft. length	F7043000	Metal	Commercial-grade (Type B) galvanized steel	-
	PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX	Q7411220	Plastic	-	-
	PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX	Q7412540	Plastic	-	-

Part name	Part no.	Codes	Standards	Listings
PEX-a pipe supports	All	IMC|UMC	ASTM E84	QAI P321 (up to 3")

Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

Related applications

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

AquaSAFE™ Fire Safety Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved