

PEX-a pipe supports

Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



| Part name  | Part no. | Material group | Subcomponent Material                      | Prop 65 label required? |
|--|----------|----------------|--|-------------------------|
| 1/2" PEX-a Pipe Support, 9-ft. length                      | F7040500 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| 3/4" PEX-a Pipe Support, 9-ft. length                      | F7040750 | Metal          | Commercial-grade (Type B) galvanized steel | No                      |
| 1" PEX-a Pipe Support, 9-ft. length                        | F7041000 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| 1 1/4" PEX-a Pipe Support, 9-ft. length                    | F7041250 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| 1 1/2" PEX-a Pipe Support, 9-ft. length                    | F7041500 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| 2" PEX-a Pipe Support, 9-ft. length                        | F7042000 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| 2 1/2" PEX-a Pipe Support, 9-ft. length                    | F7042500 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX     | Q7410510 | Plastic        | -  | -                       |
| 3" PEX-a Pipe Support, 9-ft. length                        | F7043000 | Metal          | Commercial-grade (Type B) galvanized steel | -                       |
| PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX | Q7411220 | Plastic        | -  | -                       |
| PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX    | Q7412540 | Plastic        | -  | -                       |

| Part name           | Part no. | Codes   | Standards | Listings            |
|---------------------|----------|---------|-----------|---------------------|
| PEX-a pipe supports | All      | IMC UMC | ASTM E84  | QAI P321 (up to 3") |

| Installation  | Related applications   |
|---|--|
| Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines. | PEX-a Plumbing Systems<br>Radiant Heating and Cooling Systems<br>AquaSAFE™ Fire Safety Systems |

| Footnotes | Contact information  |
|-----------|--|
| -         | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008<br>Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |