

PEX clips

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	Nylon

Product information and application use

Uponor PEX Clips are designed to suspend crosslinked polyethylene (PEX) tubing below the underside of a subfloor in a joist cavity installation.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Prop 65 label required?	Weight per UOM [lbs/UOM]
3/8" PEX Clip, 100/pkg.	F7060375	0.685	1.14	1.613	-	0.015
1/2" PEX Clip, 100/pkg.	F7051258	0.685	1.14	1.676	-	0.016
3/4" PEX Clip, 100/pkg.	F7057500	0.685	1.386	1.912	Yes	0.018
1" PEX Clip, 50/pkg.	F7051001	0.685	1.77	2.202	Yes	0.03

Installation	Related applications
Mount the PEX Clips to the underside of the subfloor in the joist cavity with the use of a drywall screw or nail. Secure the tubing to the clips at 36" intervals along the joist cavity. Refer to the Uponor Radiant Installation Handbook for additional information.	Radiant Heating and Cooling Systems

Footnotes	Contact information
-	<div><div>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</div><div>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</div></div>