

ProPEX lead-free (LF) brass to copper ball valves

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material LF Brass Cold working pressure 200.2 psi


73 °F (23 °C) at 160 psi (11 bar) Temp/pressure ratings 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)


Prop 65 label required? Yes

Product information and application use

Uponor ProPEX® lead-free (LF) brass ball valves transition brass to copper and feature inline isolation valves. These valves are not compatible with applications using glycol.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60° C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding applicationspecific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.





Part name	Part no.	Cv	End Type 1	End Type 2
ProPEX LF Brass Ball Valve, 1/2" F Adapter	EX x 1/2" Copper LF4805050	3.9	ProPEX 1/2"	Sweat 1/2"
ProPEX LF Brass Ball Valve, 3/4" F Adapter	EX x 3/4" Copper LF4807575	6.6	ProPEX 3/4"	Sweat 3/4"

Part name	Part no.	Codes	Standards	Listings
ProPEX lead-free (LF) brass to copper ball valves	All	UPC IRC IPC NPC of Canada	NSF/ANSI/CAN 372 ASTM F877 NSF/ANSI 359 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-pw-G U.P.Code

In addition, the following parts have additional codes, standards, or listings:

ProPEX LF Brass Ball Valve, 3/4" PEX

LF4807575 x 3/4" Copper Adapter

Installation	Related applications
	PEX-a Plumbing Systems
Install valve according to local building code. Do not dismantle. If soldering, aim flame away from the fitting. For more information, refer to the Uponor AquaPEX® Professional Plumbing Installation	Radiant Heating and Cooling Systems
Guide or the Radiant Floor Heating Installation Handbook.	Permafrost Protection Systems
	Turf Conditioning Systems

Footnotes		Contact information	
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
-	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	