

ProPEX lead-free (LF) brass washing machine outlet boxes

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	LF Brass
Subcomponent Material	Box: High-impact polystyrene Frame: High-impact polystyrene Support Brackets: High-impact polystyrene Valve: LF Brass
Prop 65 label required?	Yes



Product Information and application use

Uponor's ProPEX® Washing Machine Outlet Box comes with two 1/2" ProPEX hot and cold, color-coded, lead-free brass valves. The valves may be mounted from the top or bottom. The four support brackets provide easy mounting between studs. The snap-on frame (included) accommodates up to 1" drywall.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]
ProPEX Washing Machine Outlet Box, 1/2" LF Brass Valves	LF5930500	25.03	8.786	3.731	1.95

Part name	Part no.	Codes	Standards	Listings
ProPEX lead-free (LF) brass washing machine outlet boxes	LF5930500	UPC IPC NPC of Canada	NSF-372 ASME A112.18.1 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-14	cNSFus-pw-G U.P.Code

Installation

Mount in wall cavity at the desired location (e.g., behind washing machine) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

Related applications

PEX-a Plumbing Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517