υροποι


EP branch multi-port tees

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

| Technical data | |
|-----------------------|-------------------------------------|
| Vaterial | Engineered Polymer |
| End type 2 | ProPEX 1/2" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |

Product information and application use

Engineered polymer (EP) branch multi-port tees are used in hot and cold domestic potable water distribution systems. The multi-port tees are available with 3_4 " or 1" ProPEX® inlets and 1_2 " ProPEX outlets.



Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

| Part name | Part no. | End Type 1 |
|---|----------|-------------|
| 3/4" EP Branch Multi-port Tee, 3 (1/2") outlets | Q2237550 | ProPEX 3/4" |
| 3/4" EP Branch Multi-port Tee, 4 (1/2") outlets | Q2247550 | ProPEX 3/4" |
| 1" EP Branch Multi-port Tee, 4 (1/2") outlets | Q2241050 | ProPEX 1" |
| 3/4" EP Branch Multi-port Tee, 6 (1/2") outlets | Q2267550 | ProPEX 3/4" |
| 1" EP Branch Multi-port Tee, 6 (1/2") outlets | Q2261050 | ProPEX 1" |

| Part name | Part no. | Codes | Standards | Listings |
|---------------------------|----------|---|---|---|
| EP branch multi-port tees | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | ASTM E814/ULC S115 ASTM F877 ASTM F1960 CSA B137.5 ULC S102.2 ASTM E119/UL 263 NSF- 61 ULC S101 NSF-14 | IAPMO-ES HUD MR 1269 ICC-ES- PMG cNSFus- pw UL U.P.Code cQAlus P321 |

Installation

For a mounting bracket, use any product designed to mount 1" copper pipe for the $\frac{3}{4}$ " multi-port tee or 11%" copper pipe for the 1" multi-port tee. For more information, refer to the Uponor Piping Systems Installation Guide.

PEX-a Plumbing Systems

Related applications

| Footnotes | Contact i | Contact information | |
|-----------|------------------------|-------------------------|--|
| | Uponor Inc. | Uponor Ltd. | |
| | 5925 148th Street West | 6510 Kennedy Road | |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | |
| | T 800.321.4739 | T 888.594.7726 | |
| | F 952.891.2008 | F 800.638.9517 | |