

Copper valved manifold accessories - ProPEX ball valves

Project information



Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Subcomponent Material	CA 360 Brass
End type 2	Sweat 3/4"
Cold working pressure	249.5 psi
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

The Uponor ProPEX® Ball Valve products include 3/4" copper adapters and feature in-line isolation valves.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	H [inch]	I [inch]	J [inch]
ProPEX Ball Valve, 5/8" PEX x 3/4" Copper Adapter	Q5806375	2.803	1.215	1.765	0.866	0.866	1.181	0.756	0.439	0.879	0.693
ProPEX Ball Valve, 3/4" PEX x 3/4" Copper Adapter	Q5807575	2.882	1.22	1.741	0.866	0.945	1.181	0.756	0.439	0.879	0.693

Part name	Part no.	Cv	End Type 1	Weight per UOM [lbs/UOM]
ProPEX Ball Valve, 5/8" PEX x 3/4" Copper Adapter	Q5806375	6.5	ProPEX 5/8"	0.38
ProPEX Ball Valve, 3/4" PEX x 3/4" Copper Adapter	Q5807575	7	ProPEX 3/4"	0.39

Part name	Part no.	Codes	Standards	Listings
Copper valved manifold accessories - ProPEX ball valves	All	-	ASTM F1960 CSA B125 ASTM F877 ASME A112.18.1	-

Installation	Related applications
Install valve according to local building code. Do not dismantle. If soldering, aim flame away from fitting. For more information, refer to the Uponor Radiant Floor Installation Handbook.	Radiant Heating and Cooling Systems Permafrost Protection Systems Turf Conditioning Systems

Footnotes	Contact information
-	<p>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</p> <p>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</p>